

A. WINDOW SCHEDULE:

ROUGH OPENING (RD) or MASONRY OPENING (MD)	CODE	CALL OUT	STYLE	EXTERIOR	INTERIOR	HOUSE: FDH																	
						LOH			RDH			BDH			GARAGE: FDH								
						#	L*	D**	SH***	#	L*	D**	SH***	#	L*	D**	SH***	#	L*	D**	SH***		
N/A	A	PMC2918	TRANSOM	WOOD	WOOD																		
RD 2'-5" X 3'-11 5/8"	B	ICA2947	CASEMENT	ULTREX	WOOD	1	2	R	48														
RD 2'-5" X 4'-11 5/8"	C	ICA2959	CASEMENT	ULTREX	WOOD																		
RD 3'-1" X 5'-11 5/8"	D	ICA3771T	CASEMENT	ULTREX	WOOD	2	1	L	24	1	1	L	24										
						1	1	R	24	1	1	R	24										
						1	2	L	24														
						1	2	R	24														
RD 3'-11 5/8" X 4'-1"	E	ICA25472W	CASEMENT	ULTREX	WOOD																		
N/A	F	PMC5018	TRANSOM	WOOD	WOOD																		
N/A	G	PCMS618E	TRANSOM	WOOD	WOOD																		
RD 1'-9" X 5'-11 5/8"	H	ICA2171T	CASEMENT	ULTREX	WOOD	2	1	L	24														
						2	1	R	24														
RD 2'-9" X 1'-11 5/8"	I	IAWN3323	AWNING	ULTREX	WOOD																		
RD 2'-5" X 1'-11 5/8"	J	IAWN2923	AWNING	ULTREX	WOOD																		
RD 4'-9" X 1'-11 5/8"	K	IAWN29232W	AWNING	ULTREX	WOOD																		
N/A	L	PMC3712E	TRANSOM	WOOD	WOOD	2	1	F	A														
MD 3'-0 1/2" X 4'-11 3/8"	M	ICA3759	CASEMENT	ULTREX	WOOD																		
RD 4'-1" X 5'-11 5/8"	N	ICA25712WT	CASEMENT	ULTREX	WOOD																		
RD 1'-5" X 4'-7 5/8"	D	ICA1755	CASEMENT	ULTREX	WOOD																		
MD 4'-8 1/2" X 4'-11 3/8"	P	ICA29592W	CASEMENT	ULTREX	WOOD	2	2	LR	24														
RD 2'-5" X 5'-11 5/8"	Q	ICA2971T	CASEMENT	ULTREX	WOOD																		
RD 4'-9" X 5'-11 5/8"	R	ICA29712WT	CASEMENT	ULTREX	WOOD	2	1	LR	24														
MD 4'-8 1/2" X 5'-11 3/8"																							
RD 6'-1" X 3'-3 5/8"	S	ICA37392W	CASEMENT	ULTREX	WOOD																		
RD 5'-5" X 3'-3 5/8"	T	ICA33392W	CASEMENT	ULTREX	WOOD																		
MD 3'-1 1/2" X 1'-11 3/8"	U	IAWN3723	AWNING	ULTREX	WOOD																		
RD 3'-1" X 1'-11 5/8"																							
RD 1'-5" X 3'-3 5/8"	V	ICA1739	CASEMENT	ULTREX	WOOD																		
RD 1'-9" X 1'-4 1/4"	W	ICATR2116	CASEMENT	ULTREX	WOOD	4	1	F	A														
RD 2'-5" X 1'-4 1/4"	X	ICATR2916	CASEMENT	ULTREX	WOOD	4	1	F	A	MULL 2 PR.													
						4	2	F	A	MULL 2 PR.													
N/A	Y	PMC7220E	TRANSOM	WOOD	WOOD	1	1	F	A														
RD 3'-1" X 1'-7 5/8"	Z	IAWN3719	AWNING	ULTREX	WOOD																		

L*=Level (as opposed to window coding L=Left)
D**=Operator (Options: L=left, R=right, F=Fixed, A=awning)
SH***=Sill Height in inches over rough floor in inches or a=above primary unit and below header. NOTE WELL THAT ROUGH FLOOR TOP OF FACE ON L1 AND L2 SHALL BE 2' APPROXIMATELY BELOW FINISH FLOOR TOP OF FACE.

NOTE:

- Exterior frame is 2"x6" nominal overall.
- Callout preceded by a) ICA=Marvin Windows & Doors, Integrity model or b) PMC=Parrett Manufacturing Company, Inc. whereat E=elliptical, the windows which can be specified to Parrett for Parrett's drawings and owners' approval before manufacture.
- See owners in re glaze tint, notably on UV high-gain exposures.
- Windows shall have frames fastened on all sides -
 - securely to structure,
 - with solid, full-depth blocking behind each fastening,
 - with fasteners penetrating that blocking and into structure to not less than 1 linear inch.
- If a window's operable area is lockable,
 - then the locking mechanism shall be - i. operable from the interior without tools or keys and ii. clearly identifiable;
 - if the window's operable area is obstructed by window guards, security bars, grilles, or grates, i. then these obstructions shall be releasable to completely clear the operable surface, ii. without use of tools or keys, and iii. the release mechanisms in shall be maintained operable and
 - the window shall be maintained operable, and
 - the window shall be clearly identifiable from both exterior and interior.

PARRETT MANUFACTURING COMPANY, INC.
810 SECOND AVENUE EAST
P. O. BOX 440
DORCHESTER, WI 54425-0440
PH=715-654-6444
FX=715-654-6555
HTTP://PARRETTWINDOWS.COM

MARVIN WINDOWS AND DOORS
WARRAD, MN 56763
PH=888-419-0076
WWW.INTEGRITYWINDOWS.COM